02 Series Electrified Powerbolts

IPIXA Security 02 Series Electrified Powerbolts represents reliable and cost effective Access Control solution

02GF series offers electrified locks which can withstand 2000 lbs of linear positive impact. The locks are equipped with sensors to remotely monitor the status of the door. These high security locks are suitable for framless glass doors. The minimum maintenance feature & 3 years limited warranty on all models enables this range to be ideal for commercial applications.



AEL0200.GF

Product Specifications

Type

Holding Force

Operating Voltage

Cycle Testing

Current Draw

Door Status Monitoring

Operating Temperature

Timer

Weigth

Dimension

Fail Safe - Power to Lock

2000 lbs

12 VDC

500,000 Cycles

Start Current 960 mA Standby Current 130mA

Inbuilt Door Status Monitoring

- 10°C - + 55°C

Time Delay Adjustments 0, 3, 6, 9 Seconds

0.650 kg

Lock Body: 205 (L) * 35 (W) * 40 (H) mm

Bolt: 16 mm DIA, Stainless Steel



Brackets:

Stainless Steel Bracket for Frameless Glass Door

Glass Thickness: 1015-mm









IPIXA SECURITY LIMITED Kemp House, 160 City Road, London, EC1V 2NX, United Kingdom ipixa.co.uk