

02 Series

Fire Resistant Electromagnetic Locking Range

IPIXA Security 02 Series Electromagnetic Locking Range represents reliable and cost effective Access Control solution.

02 FR series offers locks with holding capacity of 600 lbs & 1200 lbs. The locks are equipped with sensors to remotely monitor the status of the door. All models are conveniently packaged with armature plate & fixing screws for both Metal & Wooden doors. The Locks are designed to meet fire/life safety applications by providing an auxiliary locking mechanism that has no moving parts.



AEL0221.FR

Product Specifications

| | |
|------------------------|--|
| Holding Force | 600 lbs |
| Operating Voltage | 12 / 24 VDC |
| Cycle Testing | 500,000 Cycles |
| Current Draw | 480 mA @ 12VDC ; 240mA @ 24 VDC |
| Door Status Monitoring | Inbuilt Door Status Monitoring with output |
| Operating Temperature | - 20°C - + 60°C |
| Operating Humidity | 0 - 95% Relative humidity |
| Certifications | CE , BS EN 15725: 2010; EN 1634 - 1 |
| Features | LED Visual Indication Back-EMF Protection Tamper Resistant Fixing Magnetic Bond Intact / Hall Sensor Automatic Voltage Surge Protection Circuitary |

Brackets:


- AEL0224.FR - Z&L Bracket for AEL0221.FR Locks
- AEL0434.FR - Semi Coverd ZL Bracket for AEL0221.FR
- AEL0435.FR - Armature Housing for AEL0221.FR
- AEL0436.FR - Armature Base for AEL0221.FR



Low Energy Consumption



FIRE RATED



Zero Residual Magnetism

Cycle Tested
500,000

★ ★ ★
3
YEARS
WARRANTY



Certified By
warringtonfire

IPIXA SECURITY LIMITED
Kemp House, 160 City Road,
London, EC1V 2NX,
United Kingdom
ipixa.co.uk