

02 Series

Fire Resistant Electromagnetic Locking Range

IPIXA Security 02 Series Electromagnetic Locking Range represents reliable and cost effective Access Control solution.

02 FR series offers locks with holding capacity of 600 lbs & 1200 lbs. The locks are equipped with sensors to remotely monitor the status of the door. All models are conveniently packaged with armature plate & fixing screws for both Metal & Wooden doors. The Locks are designed to meet fire/life safety applications by providing an auxiliary locking mechanism that has no moving parts.




AEL0222.UL

Product Specifications

Holding Force	600 lbs
Operating Voltage	12 / 24 VDC
Cycle Testing	500,000 Cycles
Current Draw	Per Door: 480 mA @ 12VDC ; 240mA @ 24 VDC
Door Status Monitoring	Inbuilt Door Status Monitoring with output
Operating Humidity	0 - 95% Relative humidity
Lock Body Dimensions	250 (L) x 47 (W) x 26 (H) mm
Armature Plate Dimensions	180 (L) x 38 (W) x 11 (H) mm



FIRE RATED



Zero Residual Magnetism

Cycle Tested 500,000

FIRE RATING 180 Minutes UL10 Listed

Features
 LED Visual Indication
 MOV surge protection
 Tamper Resistant Fixing
 Magnetic Bond Intact / Hall Sensor
 Automatic Voltage Surge Protection Circuitary

Brackets:

AEL0224.UL - Z&L Bracket for AEL0221.UL & AEL0222.UL Fire Rated Electromagnetic Locks

3 YEARS WARRANTY



Certified By



IPIXA SECURITY LIMITED
 Kemp House, 160 City Road,
 London, EC1V 2NX,
 United Kingdom
 ipixa.co.uk