

11 Series Emergency Break Glass

The Emergency Exit Break Glass is intended for quick evacuation during fire outbreak or any other emergency situations where the access control system needs to be disabled immediately. It can be used for open or closed circuits. The emergency break glass switch cuts the circuit instantly and disables the door locking mechanism when the soft plastic is pressed hard. The emergency call point is specially designed to be resettable easily using a special key.



EFS1106

Product Specifications

Dimension	: 96.6(L) x 91.5(W) x 34.5(H) mm
Output Contacts	: DPDT/2NO/2NC/2COM
Operating Voltage	: 12 / 24 VDC
Max Current Rating	: 30 mA
Operating Temperature	: -20 ~ +55 degrees celsius
Relative Humidity	: 0 ~ 95%
Material	: ABS Plastic
Hinged Protective Cover	: Present
Built-In Buzzer	: Present
Resettable - Key	: Included
Built-in buzzer	: 80 dB
LED Indicator	: Default - GREEN Active: RED



Cycle Tested
500,000

EFS1106 : *Standard Model*

EFS1106.AR : *Standard Model with Hinged Protective Cover with ENGLISH & ARABIC Text*

EFS1106.OD : *Standard Model with IP65 Rated Weatherproof Gasket*



IPIX A SECURITY LIMITED
Kemp House, 160 City Road,
London, EC1V 2NX,
United Kingdom
ipixa.co.uk